

ENDO AIR BALANCER EHB SERIES



Perfect for assembly, installation, transfer, and packing applications



- uses less power than air hoist (70% less air consumption)
- equipped with Newly-developed piston (higher durability)
- adjustable speed
- Very low noise (Diminishing workers fatigue)
- Clean exhaust air (No lubrication needed, produces no mist)

MODEL	MAX AIR PRESSURE (MPa)	MAX LIFTING CAPACITY (kg)			FEATURES
		EHB-50	EHB-85	EHB-130	
EHB-MS	0.7	55	90	140	Hoisting (pendant type)
EHB-□□ MS-A	0.7	55	90	140	Hoisting with down stop (pendant type)
EHB-□□ MS-AG	0.7	55	90	140	Hoisting with down stop (grip type)
EHB-□□D	0.7	55	90	140	With Inertia braking device (pendant type)
EHB-□□ ABC-5P-B	0.5	40	60	85	Full auto (pendant type)
EHB-□□ ABC-5G-B	0.5	40	60	85	Full auto (grip type)

- * **Maximum lifting capacity is related to air pressure. Please refer to the separate leaflets to see max. lifting capacity for each air pressure.**
- * **No down-drift even if air supply is cut off**
- * **Added safety measure – load will not fall if hoses for control handle are cut (This added safety measure is available for all models except the MS module)**
- * **Accessories: trolley or top hook (please select upon order)**
- * **Stroke: 1.8m (Cable extension is available upon request)**
- * **Cable dia: ϕ 4.76mm**
- * **Air inlet: Rc3/8**
- * **Delivery: 1 month after PO confirmation**
- **Customized lifting Jigs are available upon request**

