



Automatic Tyre Inflators

Salient Features

- Two digital readouts one for SET pressure and another for TYRE pressure
- Switchable back light LCD display to provide good visibility during night
- Display remain at last setting
- Audible and Visual end of the cycle signal indicators
- Soft touch membrane keys
- Intelligent Tyre Sensing
- Flat tyre option (for New Tubes & Punctured Tubes).



▲ Wall mountable Unit

Technical Specifications

Parameter	Comparison	
Model Name	AIROJET-1000 LCV	AIROJET-1000 HMV
Power Supply	230VAC $\pm 10\%$ at 50Hz	230VAC $\pm 10\%$ at 50Hz
System	Micro-Controller Based	Micro-Controller Based
Operation	Auto Sensing System	Auto Sensing System
Max Inlet Pressure	180 Psi	270 Psi
Working Pressure	0-100Psi	0-200Psi
Display	2 X 1" LCD With Back light	2 X 1" LCD With Back light
Display Resolution	1.0 Psi	1.0 Psi
Accuracy	± 1 Psi/ 0.07 bar of Full Scale	± 1 Psi/ 0.07 bar of Full Scale
Measuring Resolution	0.1 Psi	0.1 Psi
Indications	LED and Buzzer	LED and Buzzer
Switches	Membrane	Membrane
Power Consumption	25 VA	30VA
Output Hose	8 Meter	16 Meter
Dimensions (in mm)	260 (W) x 260 (H) x 145 (D)	260 (W) x 260 (H) x 145 (D)
Filter	0.5 Micron	0.5 Micron
Application	Two Wheelers, Car, SUV	Light and Heavy Trucks

Because of continuous development any specification mentioned above are subjected to change without notice

Application Areas:

Gas / Fuel Stations (Bunks), Automobile Garages, Transport Corporations, Automobile Manufacturing Factories, Transport Depot, Service Stations, Institutions and Puncture Shops.

Our other products



Nitrogen Tyre Inflators



▲ Air Compressor

Manufactured by:

ICON EMBEDDED CONTROLS

#374/2, Jothi Nagar, 2nd Street,

Ramanujam Nagar Extn., Uppilpalayam (P.O.),

Coimbatore - 641 015. Tamil Nadu.

Phone : +91 422 2594680 Mobile : 91 97514 56032,

E-mail : info@iconembeddedcontrols.com

Website : www.iconembeddedcontrols.com / automotivegarageequipment.com

Marketed by :

