

Intl. Ref. No.	DIAMOND Chain No.	Pitch (P)	Width Between Inner Plates (W) (Min)	Roller Dia (D) (Max)	Plate Height		Plate Thickness		Bearing Pin Dia	Width Over Bearing	Width Over Joint	Projected Bearing Area	Avg. Weight Per	Tensile Strength
					IP H1 (Max)	OP H2 (Max)	IP T1 (Max)	OP T2 (Max)	(d) (Max)	Pin (A) (Max)	Fasteners (B) (Max)	(Sq.cm)	Metre (Kg)	(Kgf) (Min)
60H-1	D 12201HE01	19.05	12.58	11.91	18	14.88	3.15	3.15	5.96	31.2	35.8	1.14	1.81	4500
80H-1	D 16201HE02	25.4	15.75	15.88	24.1	20.8	4	4	7.94	38	43.4	1.89	3	8700
100H-1	D20201HE02	31.75	18.9	19.05	30.1	26	4.7	4.7	9.54	45.4	51.5	2.75	4.38	11500
120h-1	D 24201HE02	38.1	25.23	22.23	36.2	31.2	5.56	5.56	11.11	55.1	61.7	4.1	6.61	16200
160H-1	D32201HE01	50.8	31.55	28.57	48.2	41.6	7.14	7.14	14.29	70	77.9	7.1	10.88	29000
200H-1	D40201HE01	63.5	37.85	39.67	60.3	52	8.8	8.8	19.85	93.1	103.3	12.17	20.65	52500