

Range

Model	H.P	Motor RPM	Phase	IN M3/HR	IN MT	Dis.Size in mm	Solid Handled. Size in mm
MONS10.0/6P/1	10	950	3	25-200	14.8-8.2	100	25
MONS15.0/6P/1	15	950	3	50-300	15-7	150	25
MONS20.0/6P/1	20	950	3	50-500	16-10	150	25
MONS30.0/6P/1	30	950	3	50-600	18-10	200	25
MONS10.0	10	1400	3	10-140	18.4-10	100	25
MONS15.0/1	15	1400	3	10-240	23.6-8.4	100	25
MONS20.0/1	25	1400	3	20-240	24-12.4	100	25
MONS30.0/1	30	1400	3	20-260	28.4-17	150	25

DEWATERING PUMP RANGE IN ALUMINIUM MOC**Range**

Model	H.P	Motor RPM	Phase	Capcacity in Lpm	Head in m	Dis.Size in mm	Solid Handled. Size in mm
MOD-3/10.0	10	2900	3	500-2150	24-14	150	25
MOD-3/15.0	15	2900	3	1050-2500	28-16	150	25
MOD-3/25.0	25	2900	3	1100-2750	32-18	150	25
MOD-3/30.0	30	2900	3	1200-3500	32-20	150	25

Application

- Specially designed for the drainage of sewage water/ Septic tank, Effluent treatmet, Waste water, Flood water and dirty water.

Advantage

- Portable , Light weight, Handy in operation
- Can handle solid size 25 mm
- Low maintenance cost
- Double mechanical seals arrangement reduces the chances of motor worn out