

Intel.Ref. No.	DIAMOND MAX Chain No.	Lacing Pattern	Pitch (P)	Pin Dia (d) (Max)	Plate Height (H) (Max)	Plate Thickness CO (Max)	Hole Dia (D) (Min)	Width Over Bearing Pin (A) (Max)	Avg. Weight Per Metre (Kg)	Diamond ' Max Tensile Strength (Kgf) (Min)
BL422	Q - BL 08 22	2x2						11	0.67	2800
BL423	Q - BL 08 23	2x3						13.1	0.77	2800
BL434	Q - BL 08 34	3x4						17.4	1.07	4200
BL444	Q - BL 08 44	4x4	12.7	5.09	12.07	2.08	5.12	19.5	1.21	5700
BL446	Q-BL08 46	4x6						23.75	1.51	5700
BL466	Q-BL08 66	6x6						27.99	1.81	8500
BL488	Q - BL 08 88	8x8						36.4	2.41	11400
BL 522	Q-BL1022	2x2						12.88	0.9	4000
BL523	Q-BL10 23	2x3						15.3	1.11	4000
BL534	Q-BL10 34	3x4						20.3	1.53	6100
BL544	Q-BL10 44	4x4	15.88	5.96	15.09	2.44	5.98	22.7	1.75	8100
BL546	Q-BL10 46	4x6						27.7	2.17	8100
BL566	Q-BL10 66	6x6						32.1	2.6	12200
BL588	Q-BL1088	8x8						42.5	3.44	16300