



## BOHRA ENGINEERING & TRADING CO.

NO	MODEL	IN/EX	O.E.M.	Std. D	OD	ID	LENGTH	Deg.
1	BEDFORD 220-330 Cu.In. (12V) (İN-48,20-48,30-48,50 / EX- 43,20-3,30-43,50)	İN			48	37	10	45°
		EX			43	33	10	45°
2	B.M.C. TM 30 (8V) (İN- 41,20-41,30-41,50 / EX- 36,20-6,30-36,50)	İN		40.95	41	30	10	45°
		EX			36	26	10	45°
3	B.M.C. TM 150 (12V) İN- 47,20-47,30-47,50 / EX- 41,70-41,80-42,00)	İN			47	39.5	8.7	45°
		EX			41.5	34.5	8.7	45°
4	B.M.C. KÜÇÜK FATİH 162/22 (8V) (İN-47,35-47,45-47,65 / EX- 43,95-44,05-44,25)	İN		47.15	47.2	38	7.2	30°
		EX		43.75	43.8	33.5	7.5	45°
5	B.M.C. ORTA FATİH 162/25 (12V) (İN-47,35-47,45-47,65 / EX- 43,95-44,05-44,25)	İN		47.15	47.2	38	7.2	30°
		EX		43.75	43.8	33.5	7.5	45°
6	B.M.C. DEV FATİH 214/26 (12V) (İN- 54,30-54,40-54,60 / EX- 47,40-47,50-47,70)	İN		54.08	54.1	44.5	8.5	30°
		EX		47.2	47.25	39.5	7.2	45°
7	B.M.C. VOLVO-YAVUZ (TD60-61) (12V) İN- 43,80-44,90-44,10 / EX- 41,80-41,90-42,10)	İN		43.58	43.63	35.6	6.13	30°
		EX		41.6	41.65	31.9	8.92	45°
8	CAT. D7 C/D/F, D8 H (12V) (İN- 63,80-63,90-64,10 / EX- 63,80-63,90-64,10)	İN		63.6	63.65	52.6	13	45°
		EX		63.6	63.65	50.9	13	45°
9	CAT. D7 C/D/F, D8 H (12V) (İN- 54,30-54,40-54,60 / EX- 51,10-51,20-51,40)	İN		54.08	54.15	46	11.4	30°
		EX		50.92	51	43	11.4	30°
10	DAF F85, F95, F3300 ATİ (12V) (İN- 59,35-59,45-59,65 / EX- 52,35-52,45-52,65)	İN			59.15	49.5	9.5	45°
		EX			52.15	40	9	45°
11	FIAT MURAT 124- 131, 238B (8V) (İN- 37,20-37,30-37,50 / EX- 35,70-35,80-36,00)	İN			37	29	8.5	45°
		EX			35.5	27	9	45°
12	FIAT TEMPRA 1.4 SX,SW (8V) (İN- 41,70-41,80-42,00 / EX- 33,20-33,30-33,50)	İN			41.5	35.5	8.5	45°
		EX			33	27	9	45°
13	FIAT 50 NC (8V) (İN- 50,20-50,30-50,50 / EX- 43,20-43,30-43,50)	İN			50	39	10	45°
		EX			43	33	10	45°
14	FIAT 450 - 480 TRAKTÖR (8V) (İN- 46,20-46,30-46,50 / EX- 40,20-40,30-40,50)	İN			46	40	8.5	45°
		EX			40	33	8.5	45°

15	FIAT 65.9 (8040.05) (8V) (IN- 48,20-48,30-48,50 / EX- 41,80-41,90-42,10)	IN			48	37.5	9	45°
		EX		41.6	41.65	31.9	8.92	45°
16	FIAT 415 TRAKTÖR (8V) (IN- 45,20-45,30-45,50 / EX- 40,20-40,30-40,50)	IN			45	35	10	45°
		EX			40	30	10	45°
17	FIAT 130 TIR, 673N (12V) (IN- 50,20-50,30-50,50 / EX- 43,70-43,80-44,00)	IN			50.05	44	8.5	45°
		EX			43.55	36	8.5	45°
18	FIAT 684N - 690 N4 (8200.02) (12V) (IN- 53,40-53,50-53,70 / EX- 47,40-47,50-47,70)	IN		53.14	53.2	44.1	7.3	45°
		EX		47.14	47.2	40.1	7.3	45°
19	FIAT 697N, 691, 693 (8210.02) (12V) (IN-61,40-61,50-61,70 / EX- 51,40-51,50-51,70)	IN		61.14	61.19	51.1	8.3	45°
		EX		51.14	51.19	43.1	8.3	45°
20	FORD 1.6 TAUNUS (8V) (IN- 43,20-43,30-43,50 / EX- 38,20-38,30-38,50)	IN			43	38	9	45°
		EX			38	31	9	45°
21	FORD TRANSİT 2,4 Dizel (2401E-YORK) (8V) (IN-48,20-48,30-48,50 / EX- 40,70-40,80-41,00)	IN			48	37	7.5	45°
		EX			40.5	30	7.5	45°
22	FORD TRANSİT 2,5 Dizel /T12-T15 (8V) (IN- 43,80-43,90-44,10 / EX- 38,25-38,35-38,55)	IN		43.6	43.65	36.2	6.77	45°
		EX		38.05	38.1	30.56	6.73	45°
23	FORD 1210/1211 CARGO (12V) (IN- 47,30-47,40-47,60 / EX- 40,30-40,40-40,60)	IN		47.1	47.15	40	7.8	30°
		EX		40.1	40.15	34	7.8	30°
24	FORD 3000 - 5000 TRAKTÖR (8V) (IN-52,20-52,30-52,50 / EX- 45,20-45,30-45,50)	IN			52	42	10	45°
		EX			45	34	10	45°
25	FORD ESCORT 2000 (8V) (IN- 44,70-44,80-45,00 / EX- 39,70-39,80-40,00)	IN			44.5	37	9	45°
		EX			39.5	32	9	45°
26	FORD ESCORD (16V) (IN- 29,20-29,30-29,50 / EX- 26,70-26,80-27,00)	IN			29	22.5	7	45°
		EX			26.5	21	7	45°
27	HYUNDAI H-100 (4D55) (8V) (IN-45,20-45,30-45,50 / EX- 40,20-40,30-40,50)	IN			45	36	10	45°
		EX			40	30	10	45°
28	IHI-SHIBAURA TRAKTÖR (8V) (IN-40,20-40,30-40,50 / EX- 33,70-33,80-34,00)	IN		40	40.05	30.6	6.3	45°
		EX		33.5	33.55	27.9	6.3	45°

29	INTER 654 TRAKTÖR (D206) (8V) (IN-50,20-50,30-50,50 / EX- 47,20-47,30-47,50)	IN			50	39.5	10.5	45°
		EX			47	37	10	45°
30	INTER 1800 KAMYON (12V) (IN-50,20-50,30-50,50 / EX- 47,20-47,30-47,50)	IN			50	39.5	10.5	45°
		EX			47	37	10	45°
31	ISUZU NPR 3.9L (4BD1) (8V) (IN-47,30-47,40-47,60 / EX- 39,30-39,40-39,60)	IN		47.1	47.15	39.9	7.1	45°
		EX		39.1	39.15	31	7.1	45°
32	MAGIRUS 912 (8V) (IN-45,90-46,00-46,20 / EX-40,40-40,50-40,70)	IN	2137302	45.67	45.7	36	10	45°
		EX	2137306	40.17	40.2	31	9.8	45°
33	MAN 5.20 (415) (12V) (IN-52,30-52,40-52,60 / EX-46,30-46,40-46,60)	IN		52.1	52.15	41	10	45°
		EX		46.1	46.15	35.5	10	45°
34	MAN 7.70 (12V) (IN-62,30-62,40-62,60 / EX-54,80-54,90-55,10)	IN		62.1	62.15	50	11.5	45°
		EX		54.6	54.65	42	11.5	45°
35	MAN 19.190, 5.90 (D0836, D0846) (12V) (IN-54,30-54,40-54,60 / EX-45,30-45,40-45,60)	IN		54.1	54.15	44	10.2	45°
		EX		45.1	45.15	34.5	10.2	45°
36	MAN 26.240 (12V) (IN-61,30-61,40-61,60 / EX-53,30-53,40-53,60)	IN		61.1	61.15	48	9	45°
		EX	51032030184	53.1	53.15	43	10	45°
37	MAN 26.280, 26.281 (D2566) (12V) (IN-61,30-61,40-61,60 / EX-53,30-53,40-53,60)	IN	51032030171	61.1	61.15	48	8.9	30°
		EX	51032030184	53.1	53.15	43	10	45°
38	MAN 19.462 TIR (D2840) (20V) (IN-61,30-61,40-61,60 / EX-53,30-53,40-53,60)	IN	51032030171	61.1	61.15	48	8.9	30°
		EX	51032030184	53.1	53.15	43	10	45°
39	MAN 26.230 (12V) (IN-41,50-41,60-41,80 / EX-44,25-44,35-44,55)	IN		51.07	51.12	41.5	8.5	30°
		EX		44.05	44.1	33.5	8.5	45°
40	MASSEY FERGUSON 135 (3.152) (6V) (IN-41,50-41,60-41,80 / EX-36,70-36,80-37,00)	IN		41.28	42	35	7.5	45°
		EX		36.45	37	30	8	45°
41	MASSEY FERGUSON MF 135 (6V)-HAM	IN			45	35	10	45°
		EX			40	30	10	45°
42	MASSEY FERGUSON MF 240 (8V) (IN-42,20-42,30-42,50 / EX-36,70-36,80-37,00)	IN			42	33.5	7.5	30°
		EX		36.45	37	30	8	45°

43	MASSEY FERGUSON MF 165-165-265 (8V)(IN-51,50-51,60-51,80 / EX-42,90-43,00-43,20)	IN		51.3	51.35	39.5	7.2	45°
		EX		42.7	42.75	32	9.7	45°
44	MASSEY FERGUSON MF 165 (8V)-HAM	IN			53	40	8.7	45°
		EX			45	32	10.7	45°
45	MAZDA E2200, BONGO 2000-2200 (8V)(IN-43,20-43,30-43,50 / EX-38,20-38,30-38,50)	IN			43	35	8	45°
		EX		37.95	38	30	8	45°
46	MERCEDES 302 (OM 327,OM 360) (12V)(IN-56,20-56,30-56,50 / EX-46,20-46,30-46,50)	IN	3270530431	56.11	56.15	45	10.1	45°
		EX	3270530432	46.11	46.15	36	10.1	45°
47	MERCEDES 302 S (12V)(IN-56,20-56,30-56,50- / EX-46,20-46,30-46,50)	IN			56.15	45	8.3	45°
		EX	3270530432	46.11	46.15	36	10.1	45°
48	MERCEDES 303-403 V6 E.M (OM 401) (12V)(IN-61,35-61,45-61,65 / EX-53,20-53,30-53,50)	IN	4030530331	61.15	61.2	51.1	9.3	30°
		EX	4030530032	53.12	53.15	43.1	10.1	45°
49	MERCEDES 303-403 V6 Y.M. (OM 401) (12V)(IN-60,20-60,30-60,50 / EX-53,20-53,30-53,50)	IN	4030530931	60.12	60.15	50.7	9.3	30°
		EX	4030530032	53.12	53.15	43.1	10.1	45°
50	MERCEDES 303-403 8V Y.M. (OM 422) (16V)(IN-60,20-60,30-60,50 / EX-53,20-53,30-53,50)	IN	4030530931	60.12	60.15	50.7	9.3	30°
		EX	4030530032	53.12	53.15	43.1	10.1	45°
51	MERCEDES OM 352-353 (12V)(IN-45,20-45,30-45,50 / EX-38,20-38,30-38,50)	IN	3520533131	45.1	45.15	35.4	8.3	45°
		EX	3520532032	38.1	38.15	28	8.4	45°
52	MERCEDES 2624-2628 (OM 355) (24V) (IN-51,20-51,30-51,50 / EX-40,20-40,30-40,50)	IN	3460530731	51.12	51.15	37	7.6	45°
		EX	3460530532	40.1	40.15	30.5	7.6	45°
53	MERCEDES 2517 (OM 362-364-366) (12V)(IN-44,00-44,10-44,30 / EX-38,20-38,30-38,50)	IN	3660533531	43.9	43.95	35	7.4	30°
		EX	3660532032	38.1	38.15	30	8.1	45°
54	MITSUBISHI CANTER (8V)(IN-46,20-46,30-46,50 / EX-39,20-39,30-39,50)	IN			46	39	6.8	45°
		EX			39	31.9	6.5	45°
55	MITSUBISHI L-300, L-200 (4D55) (8V)(IN-45,20-45,30-45,50 / EX-40,20-40,30-40,50)	IN			45	36	10	45°
		EX			40	30	10	45°
56	MITSUBISHI MARATON (16V)(IN-61,30-61,40-61,60 / EX-55,30-55,40-55,60)	IN	3120130491	61.1	61.15	50	7.7	45°
		EX	3120130591	55.1	55.15	45.6	7.5	45°

57	PERKINS AS 600-900 (6.354) (12V)(IN-51,50-51,60-51,80 / EX-42,90-43,00-43,20)	IN			48.35	39.5	7.6	45°
		EX	33152139	42.7	42.75	32	9.7	45°
58	PERKINS AS 250 E.M. (8V)(IN-48,55-48,65-48,85 / EX-42,90-43,00-43,20)	IN	33125121	51.3	51.35	39.5	7.2	45°
		EX	33152139	42.7	42.75	32	9.7	45°
59	PERKINS AS 600-900 (12V) - HAM DODGE	IN			53	40	8.7	45°
		EX			45	32	10.7	45°
60	PERKINS AS 950 (12V) (IN-51,50-51,60-51,80 / EX-42,90-43,00-43,20)	IN	33152155	51.3	51.35	38.5	7.2	30°
		EX	33152139	42.7	42.75	32	9.7	45°
61	RENAULT 1300-1400(8V) (IN-35,20-35,30-35,50 / EX-32,20-32,30-32,50)	IN			35	29	7	45°
		EX			32	26.5	7	45°
62	SCANIA 110(D10) (12V)(IN-60,30-60,40-60,60 / EX-52,30-52,40-52,60)	IN	131356	60.04	60.1	50	7.9	30°
		EX	131357	52.04	52.1	40	7.9	30°
63	SCANIA 111,112 (D11-DS10-DS11) (12V)(IN-56,30-56,40-56,60 / EX-52,30-52,40-52,60)	IN	247182	56.03	56.13	47.5	7.7	20°
		EX	242672	52.03	52.15	40.6	10.3	45°
64	SCANIA D8 (12V)(IN-55,20-55,30-55,50 / EX-47,40-47,50-47,70)	IN		55	55.05	45	7.6	30°
		EX		47.16	47.2	37	7.9	30°
65	SCANIA DS8 (12V) (IN-55,20-55,30-55,50 / EX-47,40-47,50-47,70)	IN		55	55.05	45	7.6	30°
		EX		47.16	47.2	36.4	7.9	45°
66	STEYR 768 TRAKTÖR (8V) (IN-55,20-55,30-55,50 / EX-47,40-47,50-47,70)	IN			45	35	10	45°
		EX			40	33	10	45°
67	TÜMÖSAN/TÜRK TRAKTÖR (8040.05) (8V) (IN-48,20-48,30-48,50 / EX-41,80-41,90-42,10)	IN			48	37.5	9	45°
		EX	465155/0	41.6	41.65	31.9	8.92	45°
68	VOLVO D60, TD61, TD63 (12V) (IN-46,30-46,40-46,60 / EX-41,80-41,90-42,00)	IN	465158/04	43.58	43.63	35.6	6.13	30°
		EX	465155/0	41.6	41.65	31.9	8.92	45°
69	VOLVO F7, F06, N86 (D70-TD70) (12V) (IN-46,30-46,40-46,60 / EX-44,30-44,40-44,60)	IN	421011/8	46.1	46.15	37.5	6.2	45°
		EX	421012/6	44.1	44.15	34	9.5	45°
70	VOLVO F10, F88, N88 (TD100) (12V) (IN-54,30-54,40-54,60 / EX-49,30-49,40-49,60)	IN	467474/3	54.06	54.1	44.3	6.7	30°
		EX	467475/0	49.08	49.13	40	11.7	45°
71	VOLVO F12, N12 (TD120-121-122) (12V) (IN-59,30-59,40-59,60 / EX-56,80-56,90-57,10)	IN	423011/6	59.12	59.17	49	6.75	30°
		EX	468448/6	56.6	56.65	45	9.5	45°