

SS AIR TOOLS

Torque Controlled Screw Driver



Lever Start Shut-off



Push Start Shut-off



Angle Type Lever Start Shut-off



Pistol Handle Trigger Start Shut-off Air Type

Ratchet Wrenches



SG-0719 - 14 1/4"
Stubby Ratchet Wrench



SM-30 3/8" Ratchet Wrench
SM-31 1/2" Ratchet Wrench



SP-809LS
Rear exhaust

MODEL	Free Speed r.p.m.	Weight g	O.A.L. mm	Dia meter mm	Noise Level ±2dBA	Air Ho. Bore Air inlet 6kg/cm ³ mm	Air Consum. m ³ /min	Torque range Kgf-cm	Std. Devia. %	Fastening Capacity	
										Machine Screw Dia	Tapping Screw Dia
T35PB	2200	430	180	29	7.4	6.35	0.28	3-20	+3	M2.4-M4.5	M2.0-M3.5
T40PB	1000	430	180	29	7.4	6.35	0.28	5-30	+3	M2.8-M5.0	M2.2-M4.0
T50PB	1400	770	215	37	7.8	9.5	0.58	7-55	+3	M2.9-M6.0	M2.6-M4.9
T55PB	1000	770	215	37	7.8	9.5	0.58	7-65	+3	M2.9-M6.4	M2.6-M5.4
R55BBP	1000	980	215	39	7.8	9.5	0.55	12-75	+3	M3.8-M6.6	M3.0-M5.4
R60BBP	550	980	215	39	7.8	9.5	0.55	30-110	+3	M5.0-M7.8	M4.0-M6.2
T60AB	550	1100	335	37	7.8	9.5	0.55	15-95	+3	M4.1-M7.0	M3.3-M6.0
T65AB	300	1100	335	37	7.8	9.5	0.55	30-180	+3	M5.1-M9.0	M4.4-M7.0

MODEL	Bolt Capacity (in/mm)	Free Speed (R.P.M.)	Torque (FT/LBS)	Square Drive	Air Inlet Thread (N.P.T.)	Air Hose Size (I.D.)	Ave. Air Consu. (CFM)	Overall Length	Weight (LBS)
SM-30	3/8"	150	50	3/8"	1/4"	3/8"	4	10"	2-1/2
SM-31	1/2"	180	50	1/2"	1/4"	3/8"	4	10"	2-1/2
SG-0719-38	3/8"	240	18	3/8"	1/4"	1/4"	3	6-5/16"	1-1/10
SP-809LS	10,11,12,13,14	170	18.44	N/A	1/4"	N/A	7.5	13.39	3.97