

PRESS BRAKE MACHINE

SPECIFICATION

MODEL	TON	BENDING CAPACITY IN MILD STEEL LENGTH-X THICKNESS	CLEARANCE BETWEEN HOUSINGS.	STROKES PER MINUTE	RAM ADJUSTMENT (m.m.)	SHUT HIGHT RAM STROKE DOWN	DEPTH OF THROAT (m.m.)	MAIN MOTOR HP / KW	RAM ADJUSTMENT MOTOR HP / KW
VKPB-151	20	1525 x 1.6	1025	30	40	170	210	3	0.5
VKPB-201	25	2030 x 1.6	1250	30	40	200	260	5	0.5
VKPB-251	30	2540 x 1.6	1550	30	40	200	260	7.5	1
VKPB-202	40	2030 x 2	1250	30	40	200	260	7.5	1
VKPB-252	40	2540 x 2	1550	30	40	200	260	7.5	1
VKPB-312	65	3150 x 2	1900	30	50	250	300	7.5	1
VKPB-153	40	1525 x 3	1025	30	60	250	300	10	1.5
VKPB-253	60	2540 x 3	1500	30	75	275	300	10	1.5
VKPB-313	80	3150 x 3	1850	30	75	275	300	12.5	2
VKPB-204	65	2030 x 4	1370	25	75	275	300	10	1.5
VKPB-254	80	2540 x 4	1535	25	75	275	300	12.5	2
VKPB-314	100	3125 x 4	1900	25	75	275	300	15	2
VKPB-256	120	2540 x 6	1700	25	75	275	300	20	2
VKPB-316	150	3125 x 6	1900	25	75	275	300	25	2
VKPB-258	150	2540 x 8	1700	25	75	275	300	25	2