

Intl. Ref. No.	DIAMOND Chain No.	Lacing Pattern	Pitch (P)	Pin Dia (d) (Max)	Plate Height (H) (Max)	Plate Thickness (Max)	Hole Dia (D) (Min)	Width Over Bearing Pin (A) (Max)	Avg. Weight Per Metre (Kg)	Tensile Strength (Kgf) (Min)
BL422	BL 08 22	2 x 2						11	0.59	2270
BL423	BL 08 23	2 x 3						13.1	0.75	2270
BL434	BL 08 34	3 x 4						17.4	1.03	3400
BL444	BL 08 44	4 x 4	12.7	5.09	12.07	2.08	5.12	19.5	1.16	4540
BL446	BL 08 46	4 x 6						23.75	1.47	4540
BL466	BL 08 66	6 x 6						27.99	1.72	6800
BL488	BL 08 88	8 x 8						36.4	2.29	9080
BL 522	BL10 22	2 x 2						12.88	0.86	3400
BL 523	BL10 23	2 x 3						15.3	1.09	3400
BL534	BL10 34	3 x 4						20.3	1.5	4990
BL544	BL10 44	4 x 4	15.88	5.96	15.09	2.44	5.98	22.7	1.68	6800
BL 546	BL10 46	4 x 6						27.7	2.15	6800
BL566	BL10 66	6 x 6						32.1	2.51	10210
BL588	BL10 88	8 x 8						42.5	3.33	13600