



THE PRIMARY SOURCE FOR ELECTRONIC INDUSTRY CALONIX ELECTRONICS PVT. LTD.

MANUFACTURERS OF : TOGGLE, ROCKER & PUSH BUTTON SWITCHES

Exporter To U.S.A.

www.calonix.net

ROCKER SWITCHES

SNAP-IN-SINGLE / DOUBLE POLE Non-illuminated



SPECIFICATIONS :

CONTACT RATINGS - 6A 250 V AC , 16A 250 V AC or 12 V DC

ELECTRIC LIFE - 10,000 Cycles min.

INSULATION RESISTANCE - 1000 Megaohms min.

DIELECTRIC STRENGTH - 2,000 V RMS @ Sea level

OPERATING TEMPERATURE : - 20° C to 65° C

MATERIAL :

CASE - High Temperature Thermoplastic

ROCKER - High Temperature Thermoplastic

CONTACT - Electrolytic Copper or Bimetal Silver


TERMINAL - Brass, Silver Plated.

SWITCHING FUNCTION

MODEL NO.	KEYWAY	KEYWAY	KEYWAY
6X01	ON	NONE	ON
6X02	ON	NONE	---
6X03	ON	OFF	ON
6X05	(ON)	OFF	(ON)
6X07	(ON)	OFF	ON
6X08	(ON)	OFF	---

() INDICATES MOMENTARY CONTACT
where X ↻ 1 for SPDT, 2 for DPDT


TERMINALS



6.3 Tab Terminal
0.75 mm Thick

BODY DETAIL

All dimensions in millimeters



Panel thickness 0.75 min - 2.5 max.

Knob available plain & with marking

COLOUR OPTION :

Body - Black, White
Knob - Black, White, Red
Green, Blue, Yellow, Grey





THE PRIMARY SOURCE FOR ELECTRONIC INDUSTRY CALONIX ELECTRONICS PVT. LTD.

MANUFACTURERS OF : TOGGLE, ROCKER & PUSH BUTTON SWITCHES

Exporter To U.S.A.

www.calonix.net

ROCKER SWITCHES

SNAP-IN SINGLE / DOUBLE POLE illuminated & non-illuminated NEW SPRING ACTION



SPECIFICATIONS :

CONTACT RATINGS - 6A 250 V AC, 16A 250 V AC or 12 V DC

ELECTRIC LIFE - 10,000 Cycles min.

INSULATION RESISTANCE - 1000 Megaohms min.

DIELECTRIC STRENGTH - 2,000 V RMS @ Sea level

OPERATING TEMPERATURE : - 20° C to 65° C

MATERIAL :

CASE - High Temperature Thermoplastic

ROCKER/LENSE - High Temperature Thermoplastic / Polycarbonet

CONTACT - Electrolytic Copper or Bimetal Silver



TERMINAL - Brass, Silver Plated.

SWITCHING FUNCTION

MODEL NO.	KEYWAY	KEYWAY	KEYWAY
N-6X01 N-6X02	ON ON	NONE NONE	ON OFF
N-6102L			
N-6202L			

where X = 1 for SPDT, 2 for DPDT

* Indicates lighted switch with neon for 6A/16A 250V AC & bulb for 12V DC



Non-illuminated : Available in flat & curved knobs

Illuminated : Available in flat knob only

Panel thickness 0.75 min - 2.5 max.

Knob available plain & with marking

* **Illuminated available in Red, Green & Amber only**

COLOUR OPTION :

Body - Black, White, Grey

Knob - Black, White, Red,

Green, Blue, Yellow, Grey

