



Model SE 5000



**AIR COOLED DIESEL GENERATOR
(New German Technology)**

Rated A/C Out Put	: 6.25 KVA
Rated A/C voltage	: 220-240
Power Factor (cosφ)	: cosφ = 1
DC Out Put Volt	: 12V / 8.3A
Phase	: Single Phase
Alternator	: Self-Excited, 2 Pole, Single Phase, Alternator (Best in its class)
Starting System	: Electric and Recoil Start
Fuel Tank Capacity	: 12.5 Litre
Fuel Consumption (g/Kw.H)	: 285.8
Continuous Running Time	: 7 Hours
Engine Type	: Single Cylinder, Vertical 4 Stroke (Made of durable Alloy)
Lubrication Oil Volume	: 1.65 Litre
Combustion System	: Direct Injection
Net Weight	: 110 Kg.



Model SE 5050



**LOW NOISE AIR COOLED DIESEL GENERATOR
(New German Technology)**

Rated A/C Out Put	: 6.25 KVA
Rated A/C voltage	: 220-240
Power Factor (cosφ)	: cosφ = 1
DC Out Put Volt	: 12V / 8.3A
Phase	: Single Phase
Alternator	: Self-Excited, 2 Pole, Single Phase, Alternator (Best in its class)
Starting System	: Electric Start
Fuel Tank Capacity	: 16 Litre
Fuel Consumption (g/Kw.H)	: 280
Continuous Running Time	: 8 Hours
Engine Type	: Single Cylinder, Vertical 4 Stroke (Made of durable Alloy)
Lubrication Oil Volume	: 1.65 Litre
Combustion System	: Direct Injection
Net Weight	: 170 Kg.