

Intl. Ref. NO.	DIAMOND Chain NO.	Pitch (P)	Width between Inner Plates (W) (Min)	Roller Dia (D) (Max)	Bearing Pin Dia (d) (Max)	Plate Height		Plate Thickness		Width Over Bearing Pin (A) (Max)	Width Over Joint Fasteners (b) (Max)	Transverse Pitch (P1)	Projected Bearing Area Sq.cm	Avg. Weight Per Metre (Kg)	Tensile Strength (Kgf) (Min)	Spares Availability
						IP (H1) (Max)	OP (H2) (Max)	IP (T1)	OP (T2)							
60H-3	D122 03	19.05	12.58	11.91	5.94	18	14.88	3.15	3.15	82.2	86.8	26.11	3.41	5.52	9720	A,b,c,d
80H-3	D 162 03	25.4	15.75	15.88	7.94	24.1	20.8	4	4	103.3	108.7	32.59	5.68	8.86	17340	a,b,c,d
100H-3	D 202 03	31.75	18.9	19.05	9.54	30.1	26	4.7	4.7	123.4	129.5	39.09	8.25	12.96	27090	b,c,d
120H-3	D 242 03	38.1	25.22	22.23	11.11	36.2	31.2	5.56	5.56	152.4	159	48.87	12.3	19.64	38850	b,c,d
140H-3	D 282 03	44.45	25.22	25.4	12.71	42.2	36.4	6.3	6.3	164.3	171.7	52.2	15.6	24.73	52740	b,c,d
160H-3	D 322 03	50.8	31.55	28.57	14.29	48.2	41.6	7.14	7.14	193.7	201.6	61.9	21 30	31.77	69360	b,c,d
100H-3	D 402 03	63.5	37.85	39.67	19.85	60.3	52	8.8	8.8	252.6	262.8	78.31	36.51	60.79	108210	b,c,d