



ATE-Activa-3401

7 Zone Security Cum Fire Panel with onboard keypad & LED.

Salient and Unique Features of Activa-3401

- Micro controller based systems
- Seven zone control panel with LED. (5 programmable zone + 1 panic zone + 1 fire zone) (programmable zone type: Instant or 24 Instant/ Manual / bypass /Bell /Home Mode)
- 1 24 hour dedicated fire zone
- Can use key instead of key pad for arm / disarm the systems. (very useful for banking industry)
- Separate entry/ exit delay time 1-99 min
- Sounder time 1-99 sec
- Individual Zone status indication on panel
- Zone omitting facility
- Built in battery backup provision
- 9 LED indication on panel
- Can use simple 24v smoke sensor with panel.

Technical Specification :

- Supply Voltage : 9V DC to 18V DC
- Quiescent Current : 60mA Max
- Operating current : 140mA max
- Maximum Load : 1.5 amp
- Operating temp : 180C to 550C
- Dimension : 11"X10"X3.5"
- Weight : Net weight 2.0 Kg (Approx) without battery
- Gross wt : 2.5 Kg (Approx)
- Mounting : Wall or flat surface
- Case Material : ABS resin plastic 1st Grade
- Color : White



"Very Much Suitable
for Establishment
like Banks
/shop/offices/flats."

- Home mode Arming
- Dedicated Panic fire & quick arm keys
- Power fails indication
- Non Volatile memory
- Open Zone Indication
- Automatic re arming after an intrusion
- Only three incorrect mode attempt allowed to disarm the systems after which systems goes into arm state
- Musical audio Indication
- Multiple sounder output
- Inbuilt tamper switch
- Computer interface through RS485
- Zone type(Bypass, delay, bell, instant, 24 hr fire zone, home/away)
- RF arming/disarming and Panic (Optional)
- Auto Bypass faulty zone on reset the system through keypad
- Seperate zone for fire in which two wire smoke sensor can be attached (example Appolo 65 series/system sensor)
- Up to 2 seperate keypad would be attachable
- Option for key operation in 6 zone panel if required in place of key pad
- 1st grade ABS plastic Body for good looking
- International Look