


### Network Dome Camera (Model No. : AV-D08)

<b>CPU</b>	Operation system	Embedded Linux OS	
	Microcomputer processor	32Bit RSIC Embedded Processor	
	Compression format	Motion-JPEG-N	
Signal system	CMOS 300,000 pixel		
Frame rate	25fps PAL 30fps NTSC		
Resolution	VGA(640*480), QVGA(320*240)		
<b>Video</b>	Video adjustment	Brightness, contrast, chroma, saturation.	
	Minimum illumination	0.1 Lux/F1.2	
	S/N ratio	>48DB (AGC off)	
	Shutter speed	1/50s(1/60s) -1/100. 000s	
<b>Network</b>	WB, BLC	Auto	
	Lens	Standard: 6mm Optional: 3.6mm 8mm	
	Network interface	RJ-45 10/100Mb self-adaptable Ethernet slot	
	Protocol	TCP/IP、HTTP、ICMP、DHCP、FTP、SMTP、PPPoE etc.	
	Online visitor	Support 5 visitors at the same time, but no limitation when using forwarder server	
	IP mode	Dynamic IP address, static IP address, PPPOE	
	Delay time	< 500 MSEL (0.50 second) in LAN	
	Shape	Ceiling-mounted, indoor use	
	Power	DC12V 1A	
	Temperature	-10~50 °C	
<b>Others</b>	Humidity	95% RH	
	Size	Item size: 142mm x 96mm (D x H) Packaging size: 170mm x 170mm x 170mm (LxWxH)	
	Weight	N.W.: 480g G.W. : 775g (Note: for real products)	
	Attachment	Adaptor CD (including manual) bracket	
<b>Alarm</b>	Input/output	1/1	
	Motion detection	Motion detection setting	
<b>System</b>	Alarm action	Support email, message, etc.	
	System requirement	Microsoft Win98 SE/ME/2000/XP、Vista. Internet Explorer 5.0, NET4.5 or above	
	System security	Supports three-level account, password, user authority management	
<b>Features</b>	DDNS (free)	Free DDNS bounded	
	Superiority	P2P technology, no user limited, save bandwidth, cell phone video monitor	
	CMS (free)	1,4,9,16,25,36, 64-channel CMS, no user limited professional CMS, centralized monitor, remote record and playback, Skype message alarm, skype telephone alarm.	
<b>Certification</b>	Certificate	ISO CCC FCC CE	

**Mumbai : 022-28972453/28481462**  
**New delhi – 011-69417843/28481462**  
**Lucknow – 0522-6590109/0144/1030**

**Offer Price**  
**Rs.6499 Plus Taxes**