

MODEL	CUTTING CAP. IN MS Length x Thickness	BLE RAKE ANGLE IN D	STROKES PER	No Of	BACK	MOTOR	OVERALL DIMENSIONS (APP)		
			MWUIE (APP)	HOLD DOWN	SAUG	HP	LENGTH	BREADTH	HEIGHT
AMTC 1	1525 X 6	0.5 – 5"	11 – 21	7	750	10	2400	1900	2200
AMTC 2	2030 X 6	0.5 – 5"	16-31	8	750	15	2700	1900	2200
AMTC 3	2540 X 6	0.5 – 5"	11 – 25	11	750	15	3200	1900	2300
AMTC-4	3125 X 6	0.5 – 5"	11 – 25	13	750	15	3800	1900	2200
AMTC 5	4000 X 6	0.5 – 5"	10 – 24	18	750	20	4500	2100	2400
AMTC-6	1525 X 8	0.5 – 5"	9 – 18	7	750	10	2400	2100	2300
AMTC – 7	2030 X 8	0.5 – 5"	11 – 21	9	750	20	2700	2100	2400
AMTC – 8	2540 X 8	0.5 – 5"	9 – 20	11	750	20	320C	2100	2400
AMTC – 9	3125 X 8	0.5 – 5"	9 – 19	13	750	20	3MM	2100	2400
AMTC – 10	4000 X 8	0.5 – 5"	8 – 18	18	750	30	4600	2300	2400
AMTC-11	1525 X 16	0.5 – 5"	7 – 15	8	750	10	2500	2100	2300
AMTC-12	2030 X 16	0.5 – 5"	11 – 17	11	750	20	2800	2200	2300
AMTC – 13	2540 X 16	0.5 – 5"	9 – 15	13	750	20	330D	2300	2300
AMTC – 14	3125 X 16	0.5 – 5"	6 – 12	15	750	20	4000	2300	2400
AMTC-15	4000 X10	0.5 – 5"	5 – 12	20	750	30	5000	2300	2500
AMTC- 16	2540 X 16	0.5 – 5"	3 – 16	13	750	25	3300	2300	2600
AMTC- 17	3125 X 16	0.5 – 5"	6 – 12	15	750	25	4000	2300	2600
AMTC 18	4000 X 13	0.5 – 5"	6 – 12	20	750	30	5000	2300	2600
AMTC- 19	2540 X 16	0.5 – 5"	7 – 10	13	750	30	3300	2300	2600
AMTC – 20	3125 X 16	0.5 – 5"	6 – 11	15	750	30	4000	2300	2800
AMTC 21	4000 X 16	0.5 – 5"	5 – 10	20	750	40	5000	2400	2700