

Reft No.	Diamond Chain No.	Pitch (P)	Width between Inner Plates (W) (Min)	Roller Dia (D) (Max)	Plate Height (H) (Max)	Plate Thickness IIP	Bearing Pin Dia (D) (Max)	Width Over Bearing Pin (A) (Max)	Width Over Joint Fasteners (B) (Max)	Projected Bearing Area (Sq.cm)	Avg. Weight Per Metre (Kg)	Tensile^ Strength (Kgf) (Min)
C2040	A 08A 01 SS 01	25.4	7.85	7.92	11.66	1.5	3.96	17.8	21.8	0.44	0.48	1045
C2042	A08A02SS 01			15.88							0.82	
C2050	A102 01 SS 01	31.75	9.4	10.16	14.58	2	5.08	20.8	25.9	0.71	0.82	1710
C2052	A102 02 SS 01			19.05							1.26	
C2060	A121 01 SS 01	38.1	12.58	11.91	18.06	2.4	5.94	26.9	31.5	1.04	1.03	2280
C2062	A121 02 SS 01			22.22							1.47	
C2080	A161 01 SS 01	50.8	15.75	15.88	24.05	3	7.92	33.5	38.9	1.77	2	3700
C2082	A161 02 SS 01			28.58							3.03	