

Intl Ref No.	Diamond Chain No.	Pitch (P)	Width between Inner Plates (W) (Min)	Roller Dia (D) (Max)	Plate Height (H)	Bearing (Max) Pin Dia (D) (Max)	Width Over Bearing Pin (A) (Max)	Width Over Joint Fasteners (B) (Max)	Transverse Pitch (PI)	Projected Bearing Area (Sq.cm)	Avg. Weight Per Metre (Kg)	Tensile Strength (Kgf) (Min)
05B-1	D05B01SS01	8	3	5	7.1	2.31	8.6	11.7	-	0.11	0.39	300
06B-1*	D06101SS01	9.53	5.72	6.35	8.2	3.28	13.5	16.8	-	0.28	0.44	650
08B-1	D08301SS01	12.7	7.75	8.51	11.8	4.45	17	20.9	-	0.5	0.7	1200
10B-1	D10101SS01	15.88	9.65	10.16	14.7	5.08	19.6	23.7	-	0.67	0.92	1450
12B-1	D12001SS01	19.05	11.68	12.07	16.1	5.72	22.7	27.3	-	0.88	1.12	1700
16B-1	D16001SS01	25.4	17.02	15.88	21	8.27	36.1	41.5	-	2.07	2.59	4000

06B-2	D06102SS01	9.53	5.72	6.35	8.2	3.28	23.8	27.1	10.24	0.56	0.74	1000 A
08B-2	D08302SS01	12.7	7.75	8.51	11.8	4.45	31	34,90	13.92	1	1.4	2160
10B-2	D10102SS01	15.88	9.65	10.16	14.7	5.08	36.2	40.3	16.59	1.34	3	2900
12B-2	D12002SS01	19.05	11.68	12.07	16.1	5.72	42.2	46.8	19.46	1.76	2.21	380(1
16B-2	D16002SS01	25.4	17.02	15.88	21	8.27	68	73.4	31.88	4.14	5.08	7590

06B-3*	D06103SS01	9.53	5.72	6.35	8.2	3.28	34	37.3	10.24	0.84	1.11	1820
08B-3	D08303SS01	12.7	7,75	8.51	11.8	4.45	44.9	48.8	13.92	1	1.31	3600
10B-3	D10103SS01	15.88	9.65	10.16	14.7	5.08	52.8	56.9	16.59	1.34	1.79	4300
12B-3	D12003SS01	19.05	11.68	12.07	16.1	5.72	61,70	66.3	19.46	1.76	2.22	5100
16B-3	D16003SS01	25.4	17.02	15.88	21	8.27	99.9	[105.30	31.88	4.14	5.03	11900