

PART NO.		MFS VT 01 WT	MFS VT 02 WT
CONTACT FORM		NO/NC/CO	NO/NC/CO
SWITCHING VOLTAGE	Max. V	200 VDC Max.	240VAC/DC
SWITCHING CURRENT	Max. A	0.5A Max	1A Max.
CARRY CURRENT	Max. A	1A Max.	2A Max.
SWITCHING CAPACITY	Max. VA	10W/VA Max.	50W/VA Max.
CONTACT RESISTANCE	Max. m	150mOhms	150mOhms
LEAD WIRE		1.5mtr PVC, 0.5mm <sup>2</sup>	1.5mtr PVC, 0.5mm <sup>2</sup>
REVERSIBLE SWITCH ACTION		NO	NO
OPERATING PRESSURE	Max. Kgcm <sup>2</sup>	1.0	1.0
OPERATING TEMPERATURE	Deg °C	-20° + 80°	-20° + 80°
MATERIAL	BODY	Nylon 6, G.F. 15%	Nylon 6, G.F. 15%
	FLOAT	Polyurethane	Polyurethane
SUITABLE SPECIFIC GRAVITY		0.75	0.75
MOUNTING HOLE DIA	mm	10.5	10.5
MOUNTING		VERTICAL	VERTICAL