

WEATHERPROOF BULLET IR CAMERA (30 m)



Features :

- Enhanced IR performance with 36/48 Pcs. 850 nm / ø5 mm LED
- Effective Range between 20-30 Mts.
- Precision Day Night Controller circuit contributes to the wonderful image of Camera both day and night separately.
- Weather proof IP66 airproof Aluminium alloy Shell.
- Auto BLC, AEC, ATW

Technical Specification			
Model	ATE-30EIR	ATE-30MIR	ATE-30PIR
Image Device	1/3" Sony Super HAD CCD		
Picture Elements	PAL : 500(H) x 582(V) NTSC : 510(H) x 492(V)	PAL : 752(H) x 582(V) NTSC : 768(H) x 494(V)	PAL : 752(H) x 582(V) NTSC : 768(H) x 494(V)
Image Size	4.9mm x 3.7mm		
Scanning Frequency	PAL : 15.625KHz(H)50Hz(V) NTSC : 15.7343KHz (H)60Hz (V)		
Horizontal Resolution	420 TVL	480TVL	540 TVL
Electronic Shutter	1/50(1/60)-1/100,000(S)		
S/N Ratio	>48db		
Minimum Illumination	F:1.2, 0.1 Lux (LED ON : 0Lux)	F:1.2, 0.1 Lux (LED ON : 0Lux)	F:1.2, 0.1 Lux (LED ON : 0Lux)
SYNC. System	Internal Sync.		
Gamma Adjust	0.45		
White Balance	Auto tracking white balance		
Lens	6 mm (Standard), Optional : 3.6/8 mm		
Lens Age	20000Hours		
Water Resistant Grade	IP 66		
Video Out	1.0Vp-p Composite, 75Ω		
Operating Voltage	DC 12V ± 10%, 1000 mA (approx.)		
Operating Temperature	0°C~50°C		

Designs and Specifications are subject to change without notice.