

Silvol Freez Oil 15, 22, 32, 46, 68, 100 Refrigeration Oils

SILVOL FREEZ OIL is formulated from specially selected lube base stocks to provide low pour point, low focal point, dryness and ready solubility in liquefied refrigerants.

Product features :

- Excellent oxidation & chemical stability
- Wide range of viscosity to suit various applications
- Prevents rust and corrosion of metal parts
- It satisfactory lubrication under moderate oxidation and thermal performance

Consumer benefits:


- Ensure high condenser efficiency
- Reduced compressor value maintenance due to less deposit
- Good thermal properties
- This oil has good demulsibility property, low deposits and sludge foaming tendency at a wide range of working temperature

Applications:

- SILVOL FREEZ OIL is recommended for all refrigeration compressors of open, hermetically selected and semi-selected industrial type, both reciprocating as well as rotary type operating at moderate evaporator temperatures and thermal loads.

Performance level: IS: 4578-1989

Available in :



SPECIFICATIONS

Sr.	Properties	Freezoil	
		46	68
1	Kinematic Viscosity, cSt@40°C	42 - 46	62 - 68
2	Viscosity Index, Min.	90	90
3	Flash Point, COC, °C Min.	200	210
4	Pour Point, °C Max.	-33	-27

* The specifications are subject to variations / development / customization