

Specifications:

| Models | K-60 | K-80 | K-100 | K-125 | K-160 | K-200 | K-250 |
|---|-------------|-------------|--------------|--------------|--------------|--------------|--------------|
| Tonnage (Tones) | 60 | 80 | 100 | 125 | 160 | 200 | 250 |
| Table Length (mm) | 2500 | 2500 | 3000 | 3000 | 3000 | 3000 | 3000 |
| Table Width (mm) | 120 | 170 | 170 | 200 | 220 | 220 | 250 |
| Distance between column (mm) | 2000 | 2000 | 2500 | 2500 | 2500 | 2500 | 2500 |
| Ram Stroke (mm) | 80 | 80 | 100 | 100 | 120 | 120 | 120 |
| Max. Distance table/ram (mm) | 180 | 200 | 200 | 200 | 200 | 210 | 210 |
| Throat Depth (mm) | 200 | 200 | 200 | 300 | 300 | 300 | 300 |
| Speed Approach, Pressing, Return (mm/sec) | 46-5-32 | 05/30/35 | 05/30/37 | 27-5-30 | 30-6-30 | 24-5-30 | 24-5-30 |
| Power (HP/1400 x rpm) | 5 | 5 | 10 | 15 | 20 | 20 | 20 |
| Overall Dimensions Approximate | | | | | | | |
| Length (mm) | 3750 | 3750 | 4250 | 4250 | 4250 | 4300 | 4300 |
| Width (mm) | 2250 | 2650 | 2700 | 3000 | 3100 | 3300 | 3300 |
| Height (mm) | 2050 | 2180 | 2180 | 2350 | 2450 | 2500 | 2800 |