



SANJANA INFOTEC

Simplifying Solutions...

SANJANA INFOTEC,
NO.45, 2nd FLOOR, FIRST MAIN,
TUNGHABHADRA STREET, NAGHARBHAVI
MAIN ROAD, MARUTINAGAR,
BANGALORE – 560 072.
MOBILE: 98802 63636 / 99450 53636 / 99028 22275
TEL – FAX: 080 – 23391984
E – MAIL: sanjanainfotech@gmail.com
Website: www.sanjanainfotec.com



RZ1070

Master-making/Printing methods	High-speed digital master-making / Fully automatic stencil printing
Original type	Book, Sheet
Original size	When using the Glass Platen: 50mm x 90mm - 310mm x 432mm When using the AF-VI:II (option) : 100mm x 148mm - 310mm x 432mm When using the DX-1 (option) : 105mm x 128mm - 297mm x 432mm
Original paper weight	When using the Glass Platen: 10kg or less When using the AF-VI:II (option) : 50g/m ² - 128g/m ² When using the DX-1 (option) : Single sided feeding 40g/m ² - 128g/m ² Double sided feeding 52g/m ² - 105g/m ²
Scanning area (max.)	297mm x 432mm
Print paper size (max./min.)	When using the Standard Stacking Tray : 100mm x 148mm - 320mm x 432mm When using the Wide Stacking Tray (option) : 100mm x 148mm -

340mm x 555mm

Paper supply capacity	1000 sheets (64g/m ²) or height less than 110mm
Print paper weight	Standard: 46g/m ² - 210g/m ² , When using the Card Feed Kit (option) : 100g/m ² - 400g/m ²
Image processing mode	Line, Photo (Standard/Portrait/Group), Duo (Line/Photo/Shadow off), Pencil (Darker/Lighter)
Resolution	Scanning resolution: 600dpi x 600dpi Printing image resolution: 600dpi x 600dpi
Master making time (for A4/Landscape/100% reproduction ratio)	Approx. 16 seconds
Printing area (max.)	291mm x 413mm
Print reproduction ratio	Preset enlargements: 163%, 141%, 122%, 116% Preset reductions: 87%, 82%, 71%, 61% Zoom : 50% - 200%, Free (individual adjustment of length/width) : 50% - 200%, Margin+ : 90% - 99%
Print speed	60 - 180ppm, Five steps variable from the control panel (60, 80, 100, 120, 130ppm) 180ppm: Selectable from the touch panel
Print position adjustment	Vertical : ±15mm, Horizontal : ±10mm
Functions ^{*1}	ADF Semi-auto ^{*2} , Admin setting, Auto-idling, Auto page renewal, Auto-process, Auto 90°rotation (B5/A4 size only), Book shadow, Confidential, Custom paper entry, D-Feed check, Digital copy count, Direct access & Selections entry, Dot process, Energy saving mode, ID counter report, ID print, Info. mail, Ink saving, Interval, Job memory, Jump wing control, Layout, Max. scan., Multi-up print, My Direct access, Output reversal ^{*3} , Overlay ^{*3} , Page split, Photo contrast, Preview, Print density, Program print, Proof, Protect, Renew page, Reservation, RISO Editor, RISO i Quality System, Scanning contrast, Scanning side ADF ^{*4} , Silent, Special paper control, Storage Memory ^{*3} , Tone curve, Top & Side margin, USB flash print, User Management, 180°rotate, 2UP

Ink supply	Fully automatic (1000ml per cartridge)
Master supply/Disposal	Fully automatic (approx. 220 sheets per roll)
Master disposal box capacity	Approx. 100 sheets
User interface	LCD touch sensitive panel with Progress Arrow indicators, front-side operation
Input port	USB 2.0 ^{*5} , Ethernet (100BASE-TX/10BASE-T)
Network protocol	TCP/IP
Sound level (100ppm at operating position)	65±1dB
Power source	100V - 120V AC, 50Hz - 60Hz <5.0A> 220V - 240V AC, 50Hz - 60Hz <2.2A>
Power consumption without option	100V - 120V Max.: 400W, During stand-by: 43W, During sleep mode: 2W 220V - 240V Max.: 380W, During stand-by: 43W, During sleep mode: 3W
Dimensions (WxDxH) without stand	When in use : 1415mm(W) x 705mm(D) x 665mm(H) When in storage : 780mm(W) x 705mm(D) x 665mm(H)
Weight without stand	Approx. 116kg