

**SPECIFICATIONS**

MODES	:	Standby, Manual, Step Track, Program Track
PROGRAM TRACK	:	Auto / Manual
SELECTIONS	:	Through membrane keypad
STEP TRACK TIME	:	
INTERVAL	:	1 to 90 Min selectable
STEP TRACK STEP SIZE	:	0.02 to 0.10 Deg selectable
LIMIT INDICATIONS	:	CW, CCW, UP, DOWN
AZ & EL SENSORS	:	13 BIT ABSOLUTE ENCODERS
ANGLE RESOLUTION	:	0.04 Deg (or) 0.01 Deg Optional
REMOTE INTERFACE	:	RS 232 / RS 485
POWER	:	230VAC, 50Hz / 50 VA max
OPERATING	:	
TEMPERATURE	:	Upto + 50°C
SIZE	:	2U (19"W x 3.5"H x 12"D)
MOUNTING	:	19 Inch Rack Mount
WEIGHT	:	Less than 6 Kgs
GPS	:	Optional
ELECTRONIC COMPASS	:	Optional
OPTION 1	:	ACU - Manual Mode Only
OPTION 2	:	ACU - Manual + Step Track
OPTION 3	:	ACU - Manual + Program Track
OPTION 4	:	ACU - Manual + Step Track + Program Track
NOTE	:	Specifications are subject to change with our notification

**COMSAT SYSTEMS PVT LTD**

Plot No: 22/A, IDA Mallapur, Hyderabad - 500 076, INDIA.  
Tel: +91-40-27152329, 27177653, 27150484 Fax: +91-40-27155045  
Email: johns@comsat-systems.com Website: www.comsat-systems.com