

**Silvol Turbine Oil 32, 37, 46, 57, 68, 78, 100
Premium Grade Turbine Oils**

SILVOL TURBINE OIL is a premium quality turbine oil made from best paraffinic base stock having excellent oxidation and chemical stability. These properties are further enhanced with incorporation of carefully selected anti-oxidants, rust inhibitors and anti-foam agents.

Product features:

- High oxidation resistance property prevents sludge deposits
- Good De-emulsification property prevents rust/corrosion of components
- Reduced oil flushing cycle time
- Good air release properties provide trouble free operations and stable pump pressure

Consumer benefits :


- Optimum viscosity to satisfy the requirements in all Turbines without gearbox designed system
- A balanced product to provide friction free movement
- Free from suspended matter, grit, water or any other impurity

Applications :

- Recommended for lubrication of steam, gas and hydro turbines. Can be used for lubrication of Turbo-Compressors, Turbo blowers etc.

Performance level : BIS 489-1983, DIN 51515, IS 1012-1987 (Reaffirmed 1993)

Available in :



SPECIFICATIONS

Sr.	Properties	Viscosity Grade						
		32	37	46	57	68	78	100
1	Kinematic Viscosity, cSt@40°C	28-	33-	41-	53-	61-	74-	90-
		35	39	50	60	74	81	110
2	Viscosity Index, Min.	100	100	100	100	100	100	100
3	Flash Point, COC, °C Min.	190	195	210	210	220	220	220
4	Pour Point, °C Max.	-9	-9	-9	-9	-9	-9	-9