

**Silvol Machine Oil - 22, 32, 46, 68, 100, 150, 220, 320, 460
General Purpose Machinery Oils**

SILVOL MACHINE OIL is a low viscosity index mineral lubricants for protecting machinery from excessive wear and provide economical lubrication.


Product features:

- Anti-rust, Anti-friction, Anti-wear, Anti-corrosion properties
- Excellent oxidation resistance and thermal stability
- Reduces wear and cuts down maintenance costs
- High resistance to foaming in services
- Hand oiling applications involving lubrication of bearings, open gears, lightly loaded slides and guide ways of machine tools
- Filter media in oil bath type air cleaners

Applications:

- Good adhesiveness and film strength
- Non-corrosive
- Flushing of automotive & industrial equipment so as to clean their all inaccessible internal surfaces
- Protective film over the surface of the metal
- Prevents rusting and corrosion of metal parts

Available in :



SPECIFICATIONS

Sr.	Properties	Viscosity Grade								
		22	32	46	68	100	150	220	320	460
1	Kinematic Viscosity, cSt@40°C	20-	29-	43-	64-	95-	145	215-	288-	440
		24	33	48	72	103	165	239	330	480
2	Flash Point, COC, °C Min.	170	190	210	220	220	225	225	230	250
3	Pour Point, °C Max.	0	0	0	0	0	0	0	0	0

* The specifications are subject to variations / development / customization