

Intl. Ref. No.	DIAMOND Chain No.	Pitch (P)	Width between Inner Plates (W) (Min)	Roller Dia (D) (Max)	Bearing Pin Dia (d) (Max)	Plate Height (H) (Max)	Width Over Bearing Pin (A) (Max)	Width Over Joint Fasteners (B) (Max)	Projected Bearing Area Sq.cm	Avg. Weight Per Metre (Kg)	Tensile Strength (Kgf) (Min)	Spares Availability
C08B	D083 01 ST 01	12.7	7.75	8.51	4.45	11.8	17	20.9	0.5	0.75	1840	a.b.od]
C10B	D101 01 ST 01	15.88	9.65	10.16	5.08	14.7	19.6	23.7	0.67	0.98	2290	A,B,CD
C12B	D120 01 ST 01	19.05	11.68	12.07	5.72	16.1	22.7	27.3	0.88	1.24	2960	a,b,cd
C16B	D160 01ST01	25.4	17.02	15.88	8.27	24.1	36.1	41.5	2.07	3.3	6120	A,B,C,D
	D160 01 ST 02	25.4	17.02	15.88	8.27	20.58	36.1	41.5	2.07	3.3	6120	A,B,C,D
C20B	D200 01 ST 01	31.75	19.56	19.05	10.19	26.4	43.2	49.3	2.91	3.91	9690	A,B,C!
C24B	D240 01 ST 01	38.1	25.4	25.4	14.63	33.4	53.4	60	5.49	7.16	16310	B,C,0
C28B	D280 01 ST 01	44.45	30.99	27.94	15.9	37	65.1	72.5	7.26	8.79	20390	B,C,0
VC32B	D320 01 ST 01	50 80	30.99	29.21	17.81	42.2	67.4	75.3	8.05	10.42	25500	b.cjd •