

Silvol Turbo 15W 40

SILVOL TURBO 15W 40 is a multigrade oil produced from carefully selected mineral bases, with new technology high-performance additives.

Product features :

- Anti-corrosion, Anti-foam, Anti-wear, Anti-friction properties
- Very high thermal & oxidation stability
- Excellent detergency & dispersancy level
- Anti thickening formula
- Reduced exhaust emissions
- Compatible with catalytic converters

Consumer benefits :

- Exceptional engine protection
- Increased engine life-time and longer oil drain interval
- Low engine maintenance & longer battery life
- Smooth running in all climatic conditions
- The High Viscosity Index Oil helps in easy cold starting and retains adequate film thickness over a wide temperature range
- Very efficient anti-deposit and anti-black sludge power which maintains a clean engine

Applications:

- SILVOL TURBO is recommended for use in heavy-duty super charged and turbo charged diesel engines and also in naturally aspirated diesel engine as crank case lubricants.
- All types of diesel passenger car / heavy duty commercial vehicles and also vehicles meeting EURO I & II norms.
- Recommended for use in new generation automobile vehicles manufactured by Tata, Ashok Leyland, Volvo, Ford, Skoda, Isuzu, Mahindra etc.
- All types of heavy earth moving machinery such as caterpillar, Cummins highway equipments, construction industry machines operating under severe duty conditions
- Fixed diesel engines, generators, power units etc.

Performance level : API CF-4/SG, MIL- L-2104 D, IS 13656: 2002

Available in :



CF4/SG GRADE

SPECIFICATIONS

Sr.No.	Properties	SAE Grade
		15W 40
1	Kinematic Viscosity, cSt@100°C	13 - 16
2	Viscosity Index, Min.	125
3	Pour Point, °C Max.	-21
4	Flash Point, COC, °C Min.	220
5	TBN, mg KOH / gm	10.0

* The specifications are subject to variations / development / customization