

SPECIFICATIONS			
PART NO.		MFS VT 01_L	MFS VT 02_L
CONTACT FORM		NO/NC/CO	NO/NC/CO
SWITCHING VOLTAGE	Max. V	200 VDC Max.	240VAC/DC
SWITCHING CURRENT	Max. A	0.5A Max	1A Max.
CARRY CURRENT	Max. A	1A Max.	2A Max.
SWITCHING CAPACITY	Max. VA	10W/VA Max.	50W/VA Max.
CONTACT RESISTANCE	Max. m	150mOhms	150mOhms
LEAD WIRE		1.5mtr PVC, 0.5mm²	1.5mtr PVC, 0.5mm²
REVERSIBLE SWITCH ACTION		NO	NO
OPERATING PRESSURE	Max. Kgcm²	1.0	1.0
OPERATING TEMPERATURE	Deg °C	-20° + 80°	-20° + 80°
MATERIAL	BODY	Stainless Steel SS 304	Stainless Steel SS 305
	FLOAT	Stainless Steel SS316L	Stainless Steel SS316L
SUITABLE SPECIFIC GRAVITY		0.7	0.7
MOUNTING HOLE DIA	mm	10.5	10.5
MOUNTING		VERTICAL	VERTICAL