

***KILEWS ELECTRIC SCREWDRIVERS***



***HIGH TORQUE COMPACT DC AUTOMATIC PUSH START CLUTCH TYPE SERIES***

Model		SKD-8300P	SKD-8400P	SKD-8500P	SKD-8300PF
Input Voltage		DC 32V			
Torque	(kgf.cm)	6-23	10-32	16-48	5-12
	(Lbf.in)	5.28-20.24	8.8-28.16	13.8-42.24	4.4-10.56
	(N.m)	0.59-2.25	0.98-3.14	1.57-4.70	0.49-1.18
Repeatable Torque Accuracy(%)		±3%			
Torque Adjustment		Stepless			
Unloaded Rotation Speed(r.p.m) ± 5%		1000	750	530	2000

Screw Size Dia(mm)	Machine Screw	2.6~4.0	3.0~5.0	4.0~6.0	2.3~3.5
	Tapping Screw	2.6~3.5	3.0~4.5	4.0~5.0	2.3~3.0
Weight (g)		700			
Length(mm)		260			
ESD (Anti-Static)		V	V	V	V
CE		V	V	V	V
RoHS		V	V	V	V
Torque Fixing Ring		KC-1	KC-1	KC-1	KC-1
Suspension Rack		KH-3	KH-3	KH-3	KH-3
Power Controller		SKP-32HL-60W ; SKP-32VR-60W			
Bit Type					

- *All of Kilews electric screwdrivers, referred to UL,CUL or CE International Safety Specifications, are made and some of models have already received formal concerning approvals.  
Some Models of Kilews full automatic electric screwdrivers can be offered with once ESD(Anti-Static)Housing required.*

