

WEATHERPROOF BULLET IR CAMERA



Features :

- Enhanced IR performance with 48 pcs. 850 nm / ø5 mm LED
- Effective Range between 15-30 Mts.
- Precision Day Night Controller circuit contributes to the wonderful image of Camera both day and night separately.
- Weather proof IP66 airproof Aluminium alloy Shell.

Specification:

Model	ATE-20MIR	ATE-20PIR(High Resolution)
Image Device	1/3" Sony Super HAD CCD	
Picture Elements	PAL : 500(H) x 582(V) NTSC : 510(H) x 492(V)	PAL : 752(H) x 582(V) NTSC : 768(H) x 494(V)
Image Size	4.9mm x 3.7mm	
Scanning Frequency	PAL : 15.625KHz(H)50Hz(V) NTSC : 15.7343KHz (H)60Hz (V)	
Horizontal Resolution	480 TVL	540TVL
Electronic Shutter	1/50(1/60)-1/100,000(S)	
S/N Ratio	>48db	
Minimum Illumination	F:1.2, 0.1 Lux (LED ON : 0Lux)	F:1.2, 1.2 Lux (LED ON : 0Lux)
SYNC. System	Internal Sync.	
Gamma Adjust	0.45	
White Balance	Auto tracking white balance	
Lens	6 or 8 mm (Standard)	
Lens Age	20000Hours	
Water Resistant Grade	IP 66	
Video Out	1.0Vp-p Composite, 75Ω	
Operating Voltage	DC 12V ± 10%, 400 mA (approx.)	
Operating Temperature	0°C~50°C	

Designs and Specifications are subject to change without notice.