

KDTA-D

DIGITAL TORQUE ANALYZERS FOR TORQUE DRIVERS



KDTA-80D

KDTA-8D / KDTA-80D

FEATURES

- Battery powered
- Checks any brand of electric driver
- Battery Charger with user selectable 100, 120 or 230V A/C adapter
- Lightweight plastic case
- kgf-cm/N·m / lb-in unit conversion
- MODE : RUN (constantly indicates torque value.)
PEAK HOLD
PEAK TO PEAK-HOLD
- AUTO RESET : Timer function available
- DATA OUTPUT : Digital output
- PRINTER : TPK-3 (Optional)
- Accuracy : $\pm 1\%$ of the indicated value + 1 increment, over the full range

| Model | Range | Increment | Measuring mode | Battery | Size | Weight (g) |
|----------|--|--------------------------------------|---------------------------------------|--------------|----------------------------------|------------|
| KDTA-8D | 3-800mN·m 0.03-8kgf·cm 0.03-7lb·in | 0.1mN·m 0.001kgf·cm 0.001lb·in | RUN Peak hold Peak to Peak hold | Rechargeable | 120 (W) × 165 (D) × 64 (H) mm | 830 |
| KDTA-80D | 3-800cN·m 0.3-80kgf·cm 0.3-70lb·in | 0.1cN·m 0.01kgf·cm 0.01lb·in | RUN Peak hold Peak to Peak hold | Rechargeable | 120 (W) × 165 (D) × 64 (H) mm | 830 |

KDTA-NDEX

DIGITAL TORQUE ANALYZERS FOR ELECTRIC DRIVERS

KDTA-N10DEX / KDTA-N100DEX

FEATURES

- Battery is rechargeable.
- For any brand of the Electric Driver
- Battery Charger is available for AC100V~230V50/60H.
- MODE : RUN (constantly indicates torque value.)
PEAK HOLD
PEAK TO PEAK-HOLD
- AUTO RESET : Timer function available
- DATA OUTPUT : Digital output
- PRINTER : TPK-3 (Optional)



* Printer and printer cable are options.

| Model | Range | Increment | Measuring mode | Battery | Size | Weight (g) |
|--------------|--|------------------------------------|---------------------------------------|--------------|----------------------------------|------------|
| KDTA-N10DEX | 1.5-100.0cN·m 0.15-10.00kgf·cm 0.13-10.00lb·in | 0.1mN·m 0.01kgf·cm 0.01lb·in | RUN Peak hold Peak to Peak hold | Rechargeable | 150 (W) × 110 (D) × 38 (H) mm | 1,000 |
| KDTA-N100DEX | 1.5-1000cN·m 1.5-100.0kgf·cm 1.3-100.0lb·in | 1cN·m 0.1kgf·cm 0.1lb·in | RUN Peak hold Peak to Peak hold | Rechargeable | 120 (W) × 165 (D) × 64 (H) mm | 1,000 |