

Intl.Ref. No.	DIAMOND Chain No.	Pitch (P)	Width between Inner Plates (W) (Min)	Roller Dia (D) (Max)	Pin Dia (d) (Max)	Plate Height (H) (Max)	Width Over Bearing Pin (A) (Max)	Width Over Joint Fasteners (B) (Max)	Avg. Weight Per Metre (Kg)	Tensile Strength (Kgf) (Min)
A2040	E08A01	25.4	7.85	7.92	3.96	11.65	17.8	21.7	0.41	1440
A2050	E10201	31.75	9.4	10.16	5.08	13.9	21.8	25.9	0.66	2270
A2060	E12101	38.1	12.58	11.91	5.94	18.1	26.9	31.5	1.03	3240
A2080	E16101	50.8	15.75	15.88	7.92	24.1	33.5	38.9	1.7	5780
A2100	E 20101	63.5	18.9	19.05	9.53	29.02	41.1	47,20	2.55	9030
A2120	E24101	76.2	25.22	22.23	11.1	34.82	50.8	57.4	4.06	12950

208B	E08301	25.4	7.75	8.51	4.45	11.65	17	20.9	0.47	1840
2108	E10101	31.75	9.65	10.16	5.08	13.9	19.6	23.7	0.68	2290
212B	E12001	38.1	11.68	12.07	5.72	15.3	22.7	27.3	0.8	2960
216B	E16001	50.8	17.02	15.88	8.27	20.65	36.1	41.5	1.42	6120
220B	E20001	63.5	19.56	19.05	10.19	26.42	43.2	49.3	2.36	9690
224B	E24001	76.2	25.4	25.4	14.63	33.4	53.4	60	4.7	16310
228B	E28001	88.9	30.99	27.94	15.9	37	65.1	72.5	6.23	20390
232B	E32001	101.6	30.99	29.21	17.81	42.2	67.4	75.3	6.72	25500