

**Silvol Indl. Lube Oil - 32, 46, 68, 100, 150, 220, 320, 460
General Purpose Lubricating Oils - Industrial**

SILVOL INDL. LUBE OIL is a high quality refined, high viscosity index paraffinic mineral oils, keeps are selected package of additives.

Product features:


- High inherent oxidation and thermal stability
- Excellent water separating properties
- High resistance to the formulation of lacquers and other oxidation products

Applications:

- Bearing lubrication of vertical and horizontal enclosed crank-case engines where additives type oils are not required.
- Open crank-case engines where compounded oils are not required.
- Sliding vane rotary machines.
- High pressure reciprocating machines.
- Circulating and bath systems where non-additive oils are not required.
- Comb boxes.

Performance level: IPSS 1-09-001-81 Specifications

Available in :



SPECIFICATIONS								
Sr.	Properties	Viscosity Grade						
		32	46	68	100	150	220	320
1	Kinematic Viscosity, cSt@40°C	29-35	42-50	62-74	90-110	135-165	200-240	290-350
2	Viscosity Index, Min.	95	95	95	95	95	95	95
3	Flash Point, COC, °C Min.	190	210	220	240	240	250	260
4	Pour Point, °C Max.	-6	-6	-6	-6	-6	-6	-6
5	FZG Failure Load Stage Min.	9	9	9	9	9	9	9

* The specifications are subject to variations / development / customization