

Detailed Technical Specifications of Industrial Tumbler Dryer:

| MODEL | CAPACITY DRY WT. 0 X DEPTH | BASKET SIZE 0 X DEPTH | DRIVE MOTOR/ BLOWER MOTOR | MAIN DOOR OPENING | STEAM CONNECTIO N CONSUMPTI ON | HEAT ELECTRIC |
|---------|-------------------------------------|--------------------------------|------------------------------------|-------------------------|--|------------------|
| DTS 15 | 15KG | | | | | |
| DTE 15 | 15KG | | 0.37 KW | | 0.5" BSP | |
| DTT 15 | 15KG | 800 X 600 | 0.37 KW | 500 | 20KG./Hr. | 12 KW |
| DTS 25 | 25KG | | | | | |
| DTE 25 | 25KG | | | | | |
| DTT 25 | 25KG | | 0.75 KW | | 0.5" BSP | |
| DTD 25 | 25KG | 950 X 850 | 0.75 KW | 650 | 40Kg./Hr. | 12 / 24 KW |
| DTS 50 | 50KG | | | | | |
| DTE 50 | 50KG | | | | | |
| DTT 50 | 50KG | | 1.5 KW | | 0.5" BSP | |
| DTD 50 | 50KG | 1250 X 990 | 1.5 KW | 800 | 80Kg./Hr. | 36 / 48 KW |
| DTS 100 | 100KG | | 2.25 KW | | | |
| DTT 100 | 100KG | | 1.5 KW | | 1" BSP | |
| DTD 100 | 100KG | 1600 X 1200 | (2 Nos.) | 1000 | 150Kg./Hr. | -- |
| DTS 200 | 200KG | | 3.75 KW | | | |
| DTT 200 | 200KG | | 2.25 KW | | 1" BSP | |
| DTD 200 | 200KG | 2030X1450 | (2 Nos.) | 1000 | 200Kg./Hr. | -- |

TING

| THERMIC FLUID CONNECTION | DIESEL CONSUMPTION | OVERALL DIMENSIONS WxDxH |
|---------------------------------|--------------------|--------------------------|
| 0.5" X 0.5" BSP 10000 Kcal/Hr. | -- | 890X1170X1740 |
| 0.5" X 0.5" BSP 20000 Kcal/Hr. | 1.5-2 Ltrs./Hr. | 1050X1460X1980 |
| 1.0" X 1.0" BSP 40000 Kcal/Hr. | 2.5-3.5 Ltrs./Hr. | 1350X1690X2300 |
| 1.5" X 1.5" BSP 80000 Kcal/Hr. | 5.5-6.5 Ltrs./Hr. | 1750X2190X2750 |
| 1.5" X 1.5" BSP 150000 Kcal/Hr. | 11-16 Ltrs/Hr. | 2210X2750X3250 |